10/19

Beschichten - Stanzen - Schneider

CMC Klebetechnik GmbH Rudolf-Diesel-Straße 4 Germany - 67227 Frankenthal 0049 (0)6233/872-300

## **TECHNICAL DATA SHEET**

CMC TYPE	CMC 15581
Product description	CMC 15581 is a baseless temperature resistant self-adhesive transfer film with moderate tack and good adhesion to preferably smooth surfaces.
Substrate	none
Adhesive colour	colourless, transparent
Adhesive thickness in mm	0.050 ± 10%
Adhesive properties	
Type of adhesive	acrylic
Adhesive strength in N/cm according to internal method PV 1006-32 (180° peel from steel)  For this test the adhesive film is transferred to a PET substrate of 50 microns thickness.	ca. 5.5
Thermal properties	
Temperature performance (max.) in °C	180
Short term temperature performance in °C (ca. 1 hour)	220
Other properties	RoHS compliant REACh compliant
Liner	siliconized paper, ca. 120 g/m²

Storage conditions: cool and dry (15 - 25°C, < 65% rel. humidity)

Quality guarantee: 12 months

The technical data are average values and subject to change without notice. They are not intended to replace user's testing.

Note on REACh: Some of our products do contain substances from the so-called candidate list. Please visit <a href="https://en.cmc.de/page/reach">https://en.cmc.de/page/reach</a> and check whether or not a purchased product is listed in our REACh statement and therefore does contain one or more SVHCs.